

Inhoudsopgave

Dikwandige lasbochten 3S 90° -EN 10253-1

2

Lasbochten

Dikwandige lasbochten 3S 90° -EN 10253-1

Geldig vanaf 17-3-2026

| Artikel | KG per -leeg- | Bruto prijs per -leeg- |
|--|---------------|------------------------|
| Dikwandige lasbochten 3S 90° -EN 10253-1 21.3x2.65 | 0,05 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 21.3x3.25 | 0,06 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 21.3x3.6 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 26.9x2.6 - P235GH | 0,07 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 26.9x3.25 | 0,08 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 33.7x3.2 - P235GH | 0,14 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 33.7x4.05 | 0,17 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 42.4x3.25 | 0,23 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 42.4x4.05 | 0,28 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 48,3x3,2 - P235GH | 0,36 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 48.3x3.65 | 0,36 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 48.3x4.05 | 0,39 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 60,3x3,2 | 0,60 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 60.3x3.6 | 0,60 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 60,3x4 - P235GH | 0,60 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 60.3x4.5 | 0,74 | * |
| Dikwandige Lasbochten 3S 90° -EN 10253-1 76.1x3.6 - P235GH | 0,96 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 76.1x4.0 | 1,06 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 76.1x4.5 | 1,19 | 147,28 |
| Dikwandige lasbochten 3S 90° -EN 10253-1 76.1x6.3 | 1,62 | 147,28 |
| Dikwandige Lasbochten 3S 90° -EN 10253-1 88.9x4.0 - P235GH | 1,51 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 88,9x4,5mm - P235GH | 1,51 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 88.9x4.85 | 1,86 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 101.6x6 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 108x6.3 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 114.3x4.5 | 4,21 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 114.3x5.6 | 3,60 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 114.3x6.3 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 114.3x8 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 114.3x8.8 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 114.3x10 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 133x6.3 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 139.7x5.6 | 5,54 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 139.7x6.3 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 139.7x6.5 | 0,00 | 414,94 |

| Artikel | KG per -leeg- | Bruto prijs per -leeg- |
|---|---------------|------------------------|
| Dikwandige lasbochten 3S 90° -EN 10253-1 139.7x7.1 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 139.7x8 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 139.7x10 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 168.3x5.6 | 8,06 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 168.3x6.3 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 168.3x7.1 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 168.3x8 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 168.3x11 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 168.3x12.5 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 193.7x8 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 193.7x10 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 219.1x8 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 219.1x10 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 219.1x12.5 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 273x8.8 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 273x10 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 273x12.5 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 323.9x8.8 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 323.9x10 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 355.6x12.5 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 355.6x20 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 406.4x12.5 | 0,10 | * |
| Dikwandige lasbochten 3S 90° -EN 10253-1 508x12.5 | 0,10 | * |